

MATERIAL SAFETY DATA SHEET
According to 91/155EEC

DURAPIPE ONE-STEP PVC-U CEMENT

1 1 Identification of the substance/preparation and of the company/undertaking

1.1 Trade Name: Durapipe One-Step PVC-U Cement
Product Code: 0.5 Litre - 03 463 395

1.2 Application of the substance / the preparation:
Adhesive

1.3 Manufacturer/Supplier:: Durapipe UK
Walsall Road
Norton Canes
Cannock
Staffordshire
WS11 9NS
Tel: +44 (0)1543 279909
Fax: +44 (0)1543 272373
enquiries@durapipe.co.uk
web: www.durapipe.co.uk

1.4 Further information obtainable from:
Durapipe UK

2. Composition/information on ingredients

Chemical characterization


Description: - Adhesive

Dangerous components:

- CAS: 109-99-9	tetrahydrofuran	50-100%
- EINECS: 203-726-8	Xi, F; R 11-36/37	
- CAS: 108-94-1	cyclohexanone	10-25%
- EINECS: 203-631-1	Xn; R 10-20	
- CAS: 78-93-3	methylethylketon	2.5-10%
- EINECS: 201-159-0	Xi, F; R 11-36-66-67	

Additional information: - For the wording of the listed risk phrases refer to section 16.

3. Hazards identification



- Xi Irritant
- F Highly flammable

Information concerning to particular hazards to man and environment:

- The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 11 Highly flammable.
R 36/37 Irritating to eyes and respiratory system.
R 66 Repeated exposure may cause skin dryness or cracking
R 67 Vapours may cause drowsiness and dizziness

Classification system: - The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4. First-aid measures

- Highly flammable (R11)
- Irritating to eyes (R36/37)
- R 66 Repeated exposure may cause skin dryness or cracking
- R 67 Vapours may cause drowsiness and dizziness

After inhalation: - Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stable in side position for transportation.

After skin contact: - Generally the product does not irritate the skin.
R 38 In case of insufficient ventilation wear suitable respiratory equipment.

After eye contact: - Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: - **Do not induce vomiting**; call for medical help immediately.

5. Fire-fighting measures

Suitable extinguishing agents:

- Water haze
- Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide

For safety reasons unsuitable extinguishing agents:
- Water with full jet

Protective equipment: - Mount respiratory protective device.

Additional information: - Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6. Accidental release measures

Person-related safety precautions:

- Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection:

- Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.

Measures for cleaning/collecting:

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
-

7. Handling and storage

Handling:

Information for safe handling:

- Ensure good ventilation/exhaustion at the workplace.
- Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

Storage:

Requirements to be met by storerooms and receptacles:

- Store in a cool location.

Information about storage in one common storage facility:

- Not required.

Further information about storage conditions:

- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

Storage class:

Class according to regulation on flammable liquids:

- A I
-

8. Exposure controls/personal protection

Additional information about design of technical facilities:

- No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

109-99-9 tetrahydrofuran

- OES Short-term value: 300 mg/m³, 100 ppm
Long-term value: 150 mg/m³, 50 ppm
IOELV, Sk

108-94-1 cyclohexanone

- OES Short-term value: 20 ppm
Long-term value: 10 ppm
IOELV, Sk

78-93-3 methylethylketon

- OES Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
IOELV, Sk,

Additional information: - The lists valid during the making were used as basis.

General protective and hygienic measures:

- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

Respiratory protection:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Suitable respiratory protective device recommended.

Protection of hands:

- Protective gloves
- Solvent resistant gloves
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

- PVC or PE gloves

Eye protection:

- Tightly sealed goggles

Body protection:

- Solvent resistant protective clothing
-

9. Physical and chemical properties

General Information

- Form: - Fluid
Colour: - According to product specification
Odour: - Characteristic

Change in condition

- Melting point/Melting range: - Undetermined.
Boiling point/Boiling range: - 65°C

Flash point: - < 0°C

Ignition temperature: - 230.0°C

Ignition temperature: - 230.0°C

Self-igniting: - Product is not selfigniting.

Danger of explosion: - Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

- Lower: - 2 Vol %
Upper: - 11.8 Vol %

Vapour pressure at 20°C: - 200.0 hPa

Density at 20°C: - 0.990 g/cm³

Solubility in / Miscibility with water: - Not miscible or difficult to mix..

Viscosity:

- Dynamic at 20°C: - 9000 mPas
Organic solvents: - 79.0 %

Solids content: - 20.9 %

10. Stability and reactivity

Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.

Dangerous reactions:

- No decomposition if used according to specifications.

Dangerous decomposition products:

- Danger of forming toxic pyrolysis products.

11. Toxicological information

Acute toxicity:

Primary irritant effect:

on the skin:

- No irritant effect.

on the eye:

- Irritating effect.

Sensitization:

- No sensitizing effects known.

Additional toxicological information:

- The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant.

12. Ecological information

General notes:

- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. Disposal considerations

Product:

Recommendation

- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation

- Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14. Transport information

Land transport ADR/RID (cross-border)

ADR/RID class:

- 3 (F1)

Danger code (Kemler):

- 33

UN-Number:

- 1133

Packaging group:

- II

Hazard label:

- 3

Description of goods:

- 1133 ADHESIVES (with a flash point below 23°C and viscous according 2.2.3.1.4) (vapor pressure at 50°C at most 110kPa)

Maritime transport IMDG:

IMDG Class:

- 3

UN Number:

- 1133

Label:

- 3

Packaging group:

- II

EMS Number:

- 3-05

Marine pollutant:

- No

Proper shipping name:

- ADHESIVES

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class:

- 3

UN/ID Number:

- 1133

Label:

- 3

Packaging group:

- II

Proper shipping name: - ADHESIVES


Remarks: - Not submit to ADR/VLG in small packing in original outside packing with UN number placed inside diamond shaped label (Limited quantity)

15. Regulatory information

Labelling according to EU guidelines:

- The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:



- Xi Irritant
- F Highly flammable
R 66 Repeated exposure may cause skin dryness or cracking
R 67 Vapours may cause drowsiness and dizziness

Risk phrases: - 11 Highly flammable.
- 36/37 Irritating to eyes and respiratory system.

Safety phrases: - 2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23/24/25 Avoid contact with skin and eyes.
37 Wear suitable gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.

National regulations: 56 Dispose of this material and its container to hazardous or special waste collection point.

Classification according to VbF: - A I

Technical instructions (air):

Class Share in %
II 50-100
III 2,5-10

Waterhazard class: - Water hazard class 1 (Self-assessment): slightly hazardous for water.

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases 10 Flammable.
11 Highly flammable.
20 Harmful by inhalation.
36 Irritating to eyes.
36/37 Irritating to eyes and respiratory system.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Health & Safety

Contact: Neil Tart