

Chlorinated Polyvinyl Chloride (PVC-C) is a modified PVC with additional high temperature strength. It has been developed to handle hot, corrosive liquids at working temperatures up to 100°C, whilst offering the ease of installation of cold solvent welded jointing.

PVC-C is inert to many mineral acids, bases, salts, paraffinic hydrocarbons, halogens and alcohols. It will not support combustion and is rated as self extinguishing. The low thermal conductivity of the material reduces moisture condensation on water lines, and will maintain the temperature of fluids with minimal insulation.

With a similar working temperature range to polypropylene, PVC-C has greater rigidity and lower thermal expansion, making it particularly suitable for above ground process pipework.

application guide

- Temperature range 5°C to 100°C
- Good mechanical strength
- Low thermal conductivity
- Odourless and tasteless
- Rigid pipes are suitable for above ground use
- Resistant to many inorganic chemicals
- Threading possible
- Sizes from 1/4" to 18" and 16mm to 160mm
- No special jointing tools required
- Non flammable and self extinguishing

- Not resistant to organic solvents

standards and approvals

Inch Sizes:	
Pipe	: ASTM F-441
Plain Fittings	: ASTM F-439
Threaded fittings	: ASTM F-437
PVC-C material	: ASTM D-1784
Metric Sizes:	
Pipe	: DIN 8079
Pipe quality & test	: DIN 8080
Plain Fittings	: DIN 8063
Threaded fittings	: BS21/DIN 2999/ISO7

PVC-C pipes and fittings are WRAS listed for use in contact with cold potable water.

section guide

Pipe - Inch Size	164
Solvent Cement, Primer, Cleaner	165
Plain Fittings - Inch Size	166
Adaptor Fittings - Inch Size	171
Saddles - Inch Size	174
Threaded Fittings - Inch Size	176
Flanges - Inch Size	179
Valves - Inch Size	
Ball Valve, True Union	180
Ball Valve Brackets, True Union	182
Ball Valve, T-Port	184
Ball Valve, L-Port	185
Gate Valve	188
Needle Valve	188
Butterfly Valve	189
Plug Gate Valve	190
Diaphragm Valve	191
Ball Valve, Laboratory	192
Globe Valve	192
Y-Pattern Valve	193
Non-Return Valve, Check	194
Non-Return Valve, Butterfly	196
Basket Strainer	196
Y-Strainer	197
Ball Valve, Electrically Actuated	198
Ball Valve, Pneumatically Actuated	199
Butterfly Valve, Electrically Actuated	200
Butterfly Valve, Pneumatically Actuated	201
Pipe - mm Size	202
Plain Fittings - mm Size	203
Adaptor Fittings - mm Size	204
Flanges - mm Size	205
Valves - mm Size	
Ball Valves	206
Diaphragm Valve	206
Butterfly Valve	207
Check Valve	207
Strainer	207

IPS Flow Systems

Seaham Grange Industrial Estate, Seaham, Co Durham, SR7 0PT, England

Tel: +44+ 191 521 3111 Fax: +44+ 191 521 3222

E-mail: sales@ipsflowsystems.com Website: www.ipsflowsystems.com