

Durapipe VKD Double Union Ball Valve

Description: In-line double union ball valve with lockable handle

Mounting: In any position

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Seals: EPDM or FPM

Seats: PTFE

End Connections: Solvent Sockets

Features: Safe blocked unions, multi-functional handle, easy actuator mounting platform and bracketing points included

Options: Electric or pneumatic actuation



MM Solvent Cement Sockets

EPDM Seals	16	H0 DKJ 305	45.19
PTFE Seats	20	H0 DKJ 306	45.42
	25	H0 DKJ 307	62.43
	32	H0 DKJ 308	71.19
	40	H0 DKJ 309	85.84
	50	H0 DKJ 310	101.22
	63	H0 DKJ 311	136.03

MM Solvent Cement Sockets

FPM Seals	16	H0 DKK 305	56.10
PTFE Seats	20	H0 DKK 306	56.35
	25	H0 DKK 307	74.17
	32	H0 DKK 308	87.44
	40	H0 DKK 309	89.07
	50	H0 DKK 310	122.27
	63	H0 DKK 311	166.80

Durapipe TKD 3-Way T-Port Ball Valve

Description: In-line horizontal T-port 3-way ball valve with lockable handle

Mounting: In any position

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Seals: EPDM or FPM

Seats: PTFE

End Connections: Solvent Sockets

Features: Safe blocked unions, multi-functional handle and easy actuator mounting platform

Options: L-Port; electric or pneumatic actuation



MM Solvent Cement Sockets

EPDM Seals	20	H0 TTJ 306	112.67
PTFE Seats	25	H0 TTJ 307	122.22
	32	H0 TTJ 308	146.31
	40	H0 TTJ 309	181.07
	50	H0 TTJ 310	201.39
	63	H0 TTJ 311	256.18

MM Solvent Cement Sockets

FPM Seals	20	H0 TTK 306	121.94
PTFE Seats	25	H0 TTK 307	134.59
	32	H0 TTK 308	161.64
	40	H0 TTK 309	203.27
	50	H0 TTK 310	238.62
	63	H0 TTK 311	303.16

Durapipe VM Diaphragm Valve

Description: In-line diaphragm valve with position indicator

Mounting: In any position

Maximum Fluid Pressure at 20°C: 10 bar

Fluid Temperature Range: 5°C - 95°C

Construction:

Body: Corzan® PVC-C

Diaphragm: EPDM, FPM or PTFE

End Connections: Solvent Spigots

Options: EPDM or PTFE diaphragm; pneumatic actuation



MM Solvent Cement Spigots

EPDM Diaphragm	20	H0 VMJ 406	79.71
	25	H0 VMJ 407	90.10
	32	H0 VMJ 408	96.19
	40	H0 VMJ 409	112.62
	50	H0 VMJ 410	157.68
	63	H0 VMJ 411	192.34
	75	H0 VMJ 412	329.82
	90	H0 VMJ 413	467.85
	110	H0 VMJ 414	710.43

MM Solvent Cement Spigots

FPM Diaphragm	20	H0 VMK 406	131.69
	25	H0 VMK 407	142.96
	32	H0 VMK 408	152.49
	40	H0 VMK 409	214.85
	50	H0 VMK 410	268.57
	63	H0 VMK 411	339.62
	75	H0 VMK 412	471.56
	90	H0 VMK 413	634.18
	110	H0 VMK 414	840.38



Actuated Valves

Durapipe PVC-C ball valves, butterfly valves and diaphragm valves are also available actuated. Please enquire for prices and information.



Durapipe FK Butterfly Valve

Description: Wafer style butterfly valve
Mounting: In any position, between flanges to BS 4504 PN10, BS 10 Table D/E or ANSI 150
Maximum Fluid Pressure at 20°C: Sizes 50mm to 63mm - 16 bar; sizes 75mm to 160mm - 10 bar
Fluid Temperature Range: 5°C - 95°C
Construction:
Body: PPGR (Polypropylene glass reinforced)
Disc: PVC-C
Seals: EPDM or FPM
End Connections: Flange mounted (flanges not included)
Options: Lug body for end of line use; FPM seals; pneumatic actuation



Lever Operated

EPDM Seals	Size	Code	Price
	50	H0 FKJ 106	165.13
	63	H0 FKJ 107	174.18
	75	H0 FKJ 108	188.77
	90	H0 FKJ 109	209.87
	110	H0 FKJ 110	250.83
	160	H0 FKJ 112	393.62

To order FPM seals, change code to FKK (prices on request)

Durapipe SR Single Union Ball Check Valve

Description: In-line ball check valve
Mounting: Vertical
Maximum Fluid Pressure at 20°C: 16 bar
Fluid Temperature Range: 5°C - 95°C
Construction:
Body: Corzan® PVC-C
Seals: EPDM or FPM
End Connections: Male solvent spigot x female solvent union
Options: EPDM seals



MM Solvent Spigot x Socket

FPM Seals	Size	Code	Price
	20	H0 SRK 306	51.94
	25	H0 SRK 307	57.66
	32	H0 SRK 308	75.08
	40	H0 SRK 309	109.92
	50	H0 SRK 310	114.70
	63	H0 SRK 311	138.45

To order EPDM seals, change code from SRK to SRJ



SR Check Valve Installation

Note that this valve must be installed at a minimum distance of 10 x nominal diameter (eg. 20" for size 2") from pump flange.

Durapipe RV Y-Type Strainer

Description: In-line sediment strainer
Mounting: In any position
Maximum Fluid Pressure at 20°C: 16 bar
Fluid Temperature Range: 5°C - 95°C
Construction:
Body: Corzan® PVC-C
Seals: EPDM or FPM
Strainer: Stainless Steel with 0.7mm mesh
End Connections: Solvent Sockets



MM Solvent Cement Sockets

FPM Seals	Size	Code	Price
	20	H0 UVK 306	94.08
	25	H0 UVK 307	107.95
	32	H0 UVK 308	131.87
	40	H0 UVK 309	173.50
	50	H0 UVK 310	249.85
	63	H0 UVK 311	276.06