

Hayward Simplex Basket Strainer

Description: In-line strainer with serviceable basket filter

Mounting: Vertical

Maximum Fluid Pressure at 20°C: 10 bar

Fluid Temperature Range: 0°C-60°C

Construction:

Body: Grey PVC-U or Transparent Eastar

Strainer Basket: PVC-U or 316 Stainless Steel

Strainer Mesh Sizes: PVC-U: 1/32", 1/16", 1/8", 3/16",
Stainless Steel: 20, 40, 60, 80, 100, 150, 200, 325 Mesh

Seals: FPM

End Connections: Solvent Socket, NPT Threaded or Flanged

Gauge: Optional



Duplex Style Available.
Please enquire for prices.

Inch Solvent Cement Sockets

PVC-U Body
PVC-U Basket

1/2	SB1050ST	278.40
3/4	SB1075ST	278.40
1	SB1100ST	278.40
1 1/2	SB1150ST	480.15
2	SB1200ST	480.15
3	SB1300S	1228.01
4	SB1400S	1228.01

NPT Female Threaded

PVC-U Body
PVC-U Basket

1/2	SB1050ST	278.40
3/4	SB1075ST	278.40
1	SB1100ST	278.40
1 1/2	SB1150ST	480.15
2	SB1200ST	480.15
3	SB1300S	1228.01
4	SB1400S	1228.01

Flanged ANSI 150

PVC-U Body
PVC-U Basket

1/2	SB1050F	320.10
3/4	SB1075F	320.10
1	SB1100F	320.10
1 1/2	SB1150F	570.66
2	SB1200F	570.66
3	SB1300F	1395.63
4	SB1400F	1539.87
6	SB1600FT	3523.91
8	SB1800FT	4642.40

NPT Female Threaded

Eastar Body
PVC-U Basket

1/2	ES100 50T	
3/4	ES100 75T	on application
1	ES101 00T	
1 1/2	ES101 50T	
2	ES102 00T	

Spare PVC-U Basket

New Style

1/2, 3/4, 1	BS11001/_	
1 1/2, 2	BS12001/_	on application
3, 4	BS14001/_	
6	BS16001/_	
8	BS18001/_	

To specify the mesh size, add to part number
e.g. 6" basket c/w 60 mesh = BS16001/60

Spare Stainless Steel Basket

New Style

1/2, 3/4, 1	BS710/_	
1 1/2, 2	BS720/_	on application
3, 4	BS740/_	
6	BS760/_	
8	BS780/_	

To specify the mesh size, add to part number, e.g. 2" basket c/w 60 mesh = BS720/60

* Note that the new style stainless steel strainer requires the additional use of a PVC-U adaptor

Optional Extras

Stainless Steel Basket

1/2 - 1	BS710(XX)	
1 1/4 - 2	BS720(XX)	on application
2 1/1 - 4	BS740(XX)	
6	BS7600(XX)	
8	BS7800(XX)	

To replace the plastic basket with a stainless steel basket, add the basket price to the strainer price (XX) Replace with mesh required. For 100 mesh replace (XX) with 100





Praher Type S4 Line Strainer

Description: In-line strainer with transparent body and union ends

Mounting: In any position

Maximum Fluid Pressure at 20°C: Sizes 3/8"/16mm to 2 1/2"/75mm - 16 bar;
3"/90mm - 10 bar

Fluid Temperature Range: 0°C-60°C

Construction:

Body: PVC-U Transparent

Seals: EPDM

Strainer: Polypropylene with 1.8mm mesh or Stainless Steel with 0.5mm, 0.75mm or 1mm mesh

End Connections: Solvent Socket, BSP Female Thread, HDPE Fusion Spigots



Inch Solvent Cement Unions

EPDM Seals
1.8mm Screen

3/8	12.0557	26.73
1/2	12.0558	28.19
3/4	12.0559	33.68
1	12.0560	39.88
1 1/4	12.0561	49.13
1 1/2	12.0562	58.96
2	12.0563	79.92
2 1/2	12.1708	166.90
3	12.0565	205.91
4	12.0350	273.81

MM Solvent Cement Unions

EPDM Seals
1.8mm Screen

16	12.1701	26.73
20	12.1702	28.19
25	12.1703	33.68
32	12.1704	39.88
40	12.1705	49.13
50	12.1706	58.96
63	12.1707	79.92
75	12.1708	166.90
90	12.1709	205.91
110	12.1710	273.81

Inch Solvent Cement Unions

EPDM Seals
no screen included

3/8	12.4735	25.00
1/2	12.4736	26.46
3/4	12.4737	32.35
1	12.4738	38.72
1 1/4	12.4739	47.68
1 1/2	12.4740	57.80
2	12.4741	79.46
2 1/2	12.4742	169.79
3	12.4743	208.08
4	12.0102	269.24

MM Solvent Cement Unions

EPDM Seals
no screen included

16	12.4707	25.00
20	12.4708	26.46
25	12.4709	32.35
32	12.4710	38.72
40	12.4711	47.68
50	12.4712	57.80
63	12.4713	79.46
75	12.4714	169.79
90	12.4715	208.08
110	12.4716	269.24

Stainless Steel Screen*

0.5mm mesh

16/3/8	50606	11.63
20/1/2	50606	11.63
25/3/4	50608	14.61
32/1	50608	14.61
40/1 1/4	50609	16.49
50/1 1/2	50610	20.10
63/2	50611	23.27
75/2 1/2	50612	35.26
90/3	50613	42.92
110/4	50613	42.92

Stainless Steel Screen*

1mm mesh

16/3/8	50622	11.63
20/1/2	50622	11.63
25/3/4	50624	14.61
32/1	50624	14.61
40/1 1/4	50625	16.49
50/1 1/2	50626	20.10
63/2	50627	23.27
75/2 1/2	50628	35.26
90/3	50629	42.92
110/4	50629	42.92

Stainless Steel Screen*

0.75mm mesh

16/3/8	50614	11.63
20/1/2	50614	11.63
25/3/4	50616	14.61
32/1	50616	14.61
40/1 1/4	50617	16.49
50/1 1/2	50618	20.10
63/2	50619	23.27
75/2 1/2	50620	35.26
90/3	50621	42.92
110/4	50621	42.92

Filter Support for Stainless Steel Screen

16/3/8	14.1474	24.26
20/1/2	14.1474	24.26
25/3/4	14.1475	25.42
32/1	14.1476	25.42
40/1 1/4	14.1477	31.10
50/1 1/2	14.1478	34.28
63/2	14.1479	37.13
75/2 1/2	14.1480	47.83
90/3	14.1481	62.87
110/4	14.1481	62.87

* Note: A filter support is required for the stainless steel screen



Spears Y-Strainer

Description: In-line strainer with transparent or grey body

Mounting: In any position

Maximum Fluid Pressure at 20°C: 10 bar

Fluid Temperature Range: 0°C-60°C

Construction:

Body: PVC-U transparent or grey

Seals: EPDM or FPM

Strainer: PVC 20 mesh

End Connections: Solvent Socket

Options: PVC or stainless steel strainer - 8, 12, 20 or 30 mesh



PVC-U Grey Body

PVC-U Screen EPDM Seals			
1/2"	YS22P_-005	33.96	
3/4"	YS22P_-007	40.31	
1"	YS22P_-010	51.02	
1 1/4"	YS22P_-012	63.72	
1 1/2"	YS22P_-015	84.96	
2"	YS22P_-020	106.21	
3"	YS22P_-030	333.05	
4"	YS22P_-040	582.29	

PVC-U Grey Body

PVC-U Screen FPM Seals			
1/2"	YS32P_-005	40.31	
3/4"	YS32P_-007	45.08	
1"	YS32P_-010	57.80	
1 1/4"	YS32P_-012	70.67	
1 1/2"	YS32P_-015	101.87	
2"	YS32P_-020	127.29	
3"	YS32P_-030	358.33	
4"	YS32P_-040	627.10	

PVC-U Transparent Body

PVC-U Screen EPDM Seals			
1/2"	YS22P_-005CL	37.36	
3/4"	YS22P_-007CL	44.35	
1"	YS22P_-010CL	56.10	
1 1/4"	YS22P_-012CL	70.11	
1 1/2"	YS22P_-015CL	93.45	
2"	YS22P_-020CL	116.83	
3"	YS22P_-030CL	349.70	
4"	YS22P_-040CL	611.40	

PVC-U Transparent Body

PVC-U Screen FPM Seals			
1/2"	YS32P_-005CL	44.35	
3/4"	YS32P_-007CL	49.59	
1"	YS32P_-010CL	63.58	
1 1/4"	YS32P_-012CL	77.73	
1 1/2"	YS32P_-015CL	112.06	
2"	YS32P_-020CL	140.03	
3"	YS32P_-030CL	376.25	
4"	YS32P_-040CL	658.46	

Prices are for PVC 20 mesh only.
Please enquire for alternative
mesh strainers.



Optional Mesh Codes

For stainless steel mesh, replace the letter 'P' with 'S'.

To specify the mesh size, add the following to the part number:

Mesh size	Hole size	Part Number
8	2.39mm	8
12	1.57mm	12
20	0.84mm	20
30	0.61mm	30

e.g. YS22P8 - 005

Durapipe RV Y-Type Strainer

Description: In-line sediment strainer

Mounting: In any position

Maximum Fluid Pressure at 20°C: 16 bar

Fluid Temperature Range: 0°C - 60°C

Construction:

Body: PVC-U

Seals: EPDM or FPM

Strainer: Polypropylene 0.6mm mesh (Optional Stainless Steel)



Inch Solvent Cement Unions

EPDM Seals			
1/2"	H0 UVE 102	37.97	
3/4"	H0 UVE 103	41.34	
1"	H0 UVE 104	55.94	
1 1/4"	H0 UVE 105	67.66	
1 1/2"	H0 UVE 106	93.25	
2"	H0 UVE 107	131.21	

MM Solvent Cement Unions

EPDM Seals			
20	H0 UVE 306	37.97	
25	H0 UVE 307	42.08	
32	H0 UVE 308	54.75	
40	H0 UVE 309	67.73	
50	H0 UVE 310	90.96	
63	H0 UVE 311	131.21	

Inch Solvent Cement Unions

FPM Seals			
1/2"	H0 UVF 102	51.42	
3/4"	H0 UVF 103	57.30	
1"	H0 UVF 104	74.57	
1 1/4"	H0 UVF 105	84.32	
1 1/2"	H0 UVF 106	134.87	
2"	H0 UVF 107	176.75	

MM Solvent Cement Unions

FPM Seals			
20	H0 UVF 306	51.42	
25	H0 UVF 307	57.30	
32	H0 UVF 308	74.57	
40	H0 UVF 309	84.32	
50	H0 UVF 310	134.87	
63	H0 UVF 311	176.74	

Also available in transparent PVC-U