


socket fusion fittings

mm sizes



Tee 90°

Size	Code	Price
16	30 056 0016 07	6.84
20	30 056 0020 07	8.07
25	30 056 0025 07	9.78
32	30 056 0032 07	14.34
40	30 056 0040 07	22.26
50	30 056 0050 07	33.59
63	30 056 0063 07	52.98
75	30 056 0075 07	99.96
90	30 056 0090 07	153.64
110	30 056 0110 07	204.84



Cap

Size	Code	Price
16	30 054 0016 07	4.92
20	30 054 0020 07	5.53
25	30 054 0025 07	6.49
32	30 054 0032 07	7.72
40	30 054 0040 07	13.32
50	30 054 0050 07	16.82
63	30 054 0063 07	25.27
75	30 054 0075 07	27.72
90	30 054 0090 07	36.47
110	30 054 0110 07	52.57



Elbow 90°

16	30 051 0016 07	3.70
20	30 051 0020 07	4.70
25	30 051 0025 07	6.08
32	30 051 0032 07	11.74
40	30 051 0040 07	18.56
50	30 051 0050 07	27.72
63	30 051 0063 07	46.85
75	30 051 0075 07	89.85
90	30 051 0090 07	113.09
110	30 051 0110 07	200.07



Reducer

Spigot x Socket

25/16	30 057 2516 07	5.19
25/20	30 057 2520 07	5.81
32/20	30 057 3220 07	7.92
32/25	30 057 3225 07	7.92
40/20	30 057 4020 07	8.96
40/25	30 057 4025 07	9.16
40/32	30 057 4032 07	10.51
50/20	30 057 5020 07	10.93
50/25	30 057 5025 07	10.93
50/32	30 057 5032 07	11.13
50/40	30 057 5040 07	11.34
63/25	30 057 6325 07	16.26
63/32	30 057 6332 07	16.26
63/40	30 057 6340 07	16.38
63/50	30 057 6350 07	16.82
75/63	30 057 7563 07	34.42
90/63	30 057 9063 07	37.42
90/75	30 057 9075 07	37.57
110/63	30 057 1163 07	53.54
110/90	30 057 1190 07	54.22



Elbow 45°

16	30 050 0016 07	4.70
20	30 050 0020 07	5.74
25	30 050 0025 07	7.72
32	30 050 0032 07	9.16
40	30 050 0040 07	15.42
50	30 050 0050 07	18.02
63	30 050 0063 07	29.91
75	30 050 0075 07	68.69
90	30 050 0090 07	102.97
110	30 050 0110 07	184.37



Socket

16	30 053 0016 07	2.94
20	30 053 0020 07	3.34
25	30 053 0025 07	4.16
32	30 053 0032 07	5.46
40	30 053 0040 07	8.07
50	30 053 0050 07	23.21
63	30 053 0063 07	33.19
75	30 053 0075 07	34.42
90	30 053 0090 07	54.50
110	30 053 0110 07	95.32



Female Adaptor

BSP or NPT female threaded

20 x 1/2	30 034 2020 07	7.85
25 x 3/4	30 034 2525 07	10.51
32 x 1	30 034 3232 07	13.66
40 x 1 1/4	30 034 4040 07	18.98
50 x 1 1/2	30 034 5050 07	25.67
63 x 2	30 034 6363 07	25.81

Code shown is for BSP
Code for NPT on request



Union

FPM O-Rings

20	30 024 1120 07	19.40
25	30 024 1125 07	24.59
32	30 024 1132 07	30.20
40	30 024 1140 07	42.06
50	30 024 1150 07	58.59
63	30 024 1163 07	87.39

Maximum Pressure PN10.



Male Adaptor

BSP or NPT male threaded

20 x 3/4	30 035 2025 07	7.30
25 x 1	30 035 2532 07	11.13
32 x 1 1/4	30 035 3240 07	13.53
40 x 1 1/2	30 035 4050 07	20.62
50 x 2	30 035 5063 07	26.36

Code shown is for BSP
Code for NPT on request

Stub Flange

DIN, ANSI or JIS standards

Size	Code	Price
16	30 052 0016 07	3.08
20	30 052 0020 07	3.34
25	30 052 0025 07	3.90
32	30 052 0032 07	4.16
40	30 052 0040 07	6.70
50	30 052 0050 07	7.92
63	30 052 0063 07	11.53
75	30 052 0075 07	33.32
90	30 052 0090 07	45.07
110	30 052 0110 07	62.81

Code shown is for DIN.
Other codes on request.

Blind Flange

Machined - Non Pressure
Drilled to BS4504 PN10

20	30 334 0020 00	74.16
25	30 334 0025 00	78.26
32	30 334 0032 00	83.02
40	30 334 0040 00	107.60
50	30 334 0050 00	116.49
63	30 334 0063 00	129.61
75	30 334 0075 00	146.12
90	30 334 0090 00	181.63
110	30 334 0110 00	205.53

Also available drilled to JIS standards. Please enquire for details.

Gasket

EPDM

20	861-_-005	0.47
25	861-_-007	0.55
32	861-_-010	0.60
40	861-_-012	0.75
50	861-_-015	0.91
63	861-_-020	1.56
75	861-_-025	1.91
90	861-_-030	2.05
110	861-_-040	2.98

Complete code when ordering
Insert 'I' for NP10/16; 'A' for ANSI 150;
'E' for Table D/E

Gasket

FPM

20	862-_-005	2.12
25	862-_-007	3.28
32	862-_-010	4.33
40	862-_-012	6.94
50	862-_-015	7.59
63	862-_-020	10.00
75	862-_-025	14.47
90	862-_-030	18.88
110	862-_-040	32.21

Complete code when ordering
Insert 'I' for NP10/16; 'A' for ANSI 150;
'E' for Table D/E

Backing Ring Table D/E

Galvanised mild steel

20	860-005-11E	5.39
25	860-007-11E	6.10
32	860-010-11E	6.41
40	860-012-11E	6.60
50	860-015-11E	8.10
63	860-020-11E	11.49
75	860-025-11E	17.17
90	860-030-11E	17.45
110 D	860-040-11D	22.56
110 E	860-040-11E	22.56

Backing Ring NP10/16

Galvanised mild steel

20	860-005-11NP	6.10
25	860-007-11NP	6.46
32	860-010-11NP	7.67
40	860-012-11NP	8.15
50	860-015-11NP	8.94
63	860-020-11NP	12.63
75	860-025-11NP	17.29
90	860-030-11NP	20.00
110	860-040-11NP	25.11

Backing Ring ANSI 150

Galvanised mild steel

20	860-005-11A	6.10
25	860-007-11A	6.46
32	860-010-11A	7.67
40	860-012-11A	8.15
50	860-015-11A	8.94
63	860-020-11A	12.63
75	860-025-11A	17.29
90	860-030-11A	20.00
110	860-040-11A	25.11

Backing Ring NP10

Polypropylene with steel core

20	11 014 0020 11	6.41
25	11 014 0025 11	7.04
32	11 014 0032 11	9.01
40	11 014 0040 11	11.42
50	11 014 0050 11	13.34
63	11 014 0063 11	15.47
75	11 014 0075 11	17.17
90	11 014 0090 11	20.28
110	11 014 0110 11	24.12

Backing Ring ANSI 150

Polypropylene with steel core

20	11 013 0020 11	6.41
25	11 013 0025 11	7.04
32	11 013 0032 11	9.01
40	11 013 0040 11	11.42
50	11 013 0050 11	13.34
63	11 013 0063 11	15.47
75	11 013 0075 11	17.17
90	11 013 0090 11	20.28
110	11 013 0110 11	24.12



Pressure Ratings

PVDF socket fusion fittings are suitable for use at pressures up to 20 bar at 20°C except where shown. Threaded fittings are de-rated to 12 bar.