

Staufix Installation in an exposed wastewater pipe

Products

Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
<p>Illustration shows <input type="checkbox"/></p> <p>Installation area 650 x 300 mm</p>	<p>Twin flap backwater valve <i>Staufix</i> made of polymer, Ø... with emergency closure</p> <p>1 with two polymer flaps</p> <p>2 with one polymer flap and one stainless steel rodent protection flap (version R)</p> <p>Twin flaps, self-closing, one of which can be locked by hand as an emergency closure. Inlet/outlet for connection to PVC pipe according to EN 1566-1.</p> <p>Ø 110 L: 355 H: 180+25 AxB: 205 x 155 mm Ø 125 L: 405 H: 240+40 AxB: 270 x 200 mm Ø 160 L: 450 H: 240+40 AxB: 270 x 200 mm Ø 200 L: 530 H: 278+50 AxB: 353 x 248 mm</p> <p> EN 13564 Type 2</p>	<p>1 Ø 110 Ø 125 Ø 160 Ø 200</p> <p>2 Ø 110 Ø 125 Ø 160</p>	<p>73100 73125 73150 73200</p> <p>73100R 73125R 73150R</p>
<p>Illustration shows <input type="checkbox"/></p> <p>Installation area 650 x 300 mm</p>	<p>Single flap backwater valve <i>Staufix</i> made of polymer, Ø... with emergency closure</p> <p>1 with one polymer flap</p> <p>2 with one stainless steel rodent protection flap (version R)</p> <p>Self-closing flap, can be locked by hand as an emergency closure. Inlet/outlet for connection to PVC pipe according to EN 1566-1.</p> <p>Ø 100 L: 355 H: 180+25 AxB: 205 x 155 mm Ø 110 L: 355 H: 180+25 AxB: 205 x 155 mm Ø 125 L: 405 H: 240+40 AxB: 270 x 200 mm Ø 160 L: 450 H: 240+40 AxB: 270 x 200 mm Ø 200 L: 530 H: 278+50 AxB: 353 x 248 mm</p> <p> EN 13564 Type 1</p>	<p>1 Ø 100 Ø 110 Ø 125 Ø 160 Ø 200</p> <p>2 Ø 110 Ø 125 Ø 160</p>	<p>77100 72100 72125 72150 72200</p> <p>72100R 72125R 72150R</p>
<p>Installation area 650 x 300 mm</p>	<p>Single flap backwater valve <i>Staufix</i> made of polymer, Ø... without emergency closure</p> <p><input type="checkbox"/> with one polymer flap</p> <p>Self-closing flap. Inlet/outlet for connection to PVC pipe according to EN 1566-1.</p> <p>Ø 110 L: 355 H: 170 A x B: 205 x 155 mm Ø 110 L: 355 H: 170 A x B: 205 x 155 mm Ø 125 L: 405 H: 230 A x B: 270 x 200 mm Ø 160 L: 450 H: 230 A x B: 270 x 200 mm Ø 200 L: 530 H: 278 A x B: 353 x 248 mm</p> <p> EN 13564 Type 0</p>	<p>Ø 100 Ø 110 Ø 125 Ø 160 Ø 200</p>	<p>76100 71100 71125 71150 71200</p>
<p>Installation area 650 x 300 mm</p>	<p>Clean out <i>Staufix</i> made of polymer, Ø... upgradable to all <i>Staufix</i> model backwater valves</p> <p>Ø 110 L: 355 H: 170 AxB: 205 x 155 mm Ø 125 L: 405 H: 230 AxB: 270 x 200 mm Ø 160 L: 450 H: 230 AxB: 270 x 200 mm Ø 200 L: 530 H: 278 AxB: 353 x 248 mm</p>	<p>Ø 110 Ø 125 Ø 160 Ø 200</p>	<p>70100 70125 70150 70200</p>

Installation example *Staufix*



Staufix twin flap backwater valve - the classical item in the KESSEL backwater range and the successful original. The current model is made of ABS, completely corrosion-free and can be serviced without tools. Protects individual drainage fixtures such as shower, sink and washing machine below the backwater level. Installation in the concrete slab with upper section Art. # 32500 and two cover plates Art. # 30004 S or for installation in an exposed wastewater pipe.

Professional advantages

- **Tool-free servicing**
- **Everything made of polymer material - corrosion-free**
- **Backwater flap** made of stainless steel to keep rats and vermin out
- **Perfect for renovation**
Other valves with large drops are difficult to install. *Staufix* offers minimal drop between inlet/outlet (7 mm).
- Can be **retrofitted/converted** after installation



Scan this QR code to directly view the corresponding product video.



Staufix

Accessories

Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
	Cover plate, class L 15 <input type="checkbox"/> black Upper section Height = 220 mm for article numbers: 70 100, 70 125, 70 150, 70 200, 71 100, 71 125, 71 150, 71 200, 72 100, 72 125, 72 150, 72 200, 72 100R, 72 125R, 72 150R, 73 100, 73 125, 73 150, 73 200, 73 100R, 73 125R, 73 150R	-	30004 S
	Conversion kit The <i>Staufix</i> clean out body can be converted to a <i>Staufix</i> twin flap backwater valve by means of two backwater flaps 1 , the insert flap housing 2 and the lockable cover 3 . Please note: 2x backwater flap 70 205 and the lockable cover are required for the Ø 200 version.	3 Lockable cover incl. emergency closure and sealing gasket: Ø 110 Ø 125 Ø 160 Ø 200	70 261 70 262 70 262 70 203
	Conversion kit The <i>Staufix</i> clean out body can be converted to a <i>Staufix</i> single flap backwater valve with emergency closure by means of the backwater flap 1 , insert flap housing 2 and the lockable cover 3 .	2 Insert flap housing: Ø 110 Ø 125 Ø 160 Ø 200	70 241 70 242 70 242 70 205
For <i>Staufix</i> from 04/2005 	Conversion kit The <i>Staufix</i> clean out body can be converted to a <i>Staufix</i> single flap backwater valve by means of a backwater flap 1 .	1 Backwater flap: Ø 110 Ø 125 Ø 160 Ø 200	70 231 70 232 70 232 70 205
	Stainless steel rodent protection flap for article numbers: 70 100, 70 125, 70 150, 71 100, 71 125, 71 150 72 100, 72 125, 72 150, 73 100, 73 125, 73 150	Ø 110 Ø 125 Ø 160	70 233 70 234 70 234