

polyethylene

Polyethylene is now in widespread use for industrial pipework systems, as well as for buried gas and water pipelines, where it is the dominant material.

One of the major benefits is that Polyethylene is virtually unbreakable due to impact at temperatures above 5°C, and remains very tough at temperatures as low as -40°C. It is also exceptionally resistant to abrasion, and will outlast steel or other hard materials in most slurry handling applications.

Polyethylene is relatively low in weight, and its flexibility makes it suitable for temporary pipelines which are lain on rough ground or where buried in unstable ground conditions.

It has very good chemical resistance, and will withstand most acids and caustic substances. It is insoluble in all organic and inorganic solvents at 20°C, but it will not resist strong oxidising acids.

The Agruline range of PE now includes PE100-RC which has exceptional resistance against slow crack growth.

Polyethylene is joined by heat, and both socket fusion and butt fusion welding equipment is available for sale or hire.

application guide

- Wide range of sizes from 10mm to 1400mm
- High impact resistance
- Temperature range from -40°C to +60°C
- Exceptionally resistant to abrasion
- Non-toxic
- Resistant to many acids, alkalis, organic and inorganic solvents
- Flexible and therefore suitable for buried or surface pipelines
- UV resistant

- Not resistant to strong oxidising acids
- Special welding equipment required
- Above ground pipes require a lot of support

standards and approvals

Pipe : DIN 8074 - dimensions
: DIN 8075 - testing
Fittings : DIN 16963

section guide

Pipe - mm Sizes	285
Socket Fusion Fittings - mm Sizes	286
Socket Fusion Flanges - mm Sizes	287
Electrofusion Fittings - mm Sizes	288
Fusion Spigot Fittings - mm Sizes	290
Fusion Spigot Flanges - mm Sizes	297
Ball Valve	299
Electrically Conductive Pipe and Fittings	302
FM Approved Pipe and Fittings	304