

PVCC Pipe Inch Sizes Corzan Pipe Schedule 40

3 & 6 metre lengths. Threading not recommended.



Corzan Pipe Schedule 40

3 & 6 metre lengths. Threading not recommended.

Size	Code	Maximum Pressure (bar)	O.D. (mm)	Minimum Wall (mm)	Weight /m
1/4	400-002C	53	13.8	2.2	0.11
3/8	400-003C	42	17.2	2.3	0.22
1/2	400-005C	41	21.4	2.8	0.27
3/4	400-007C	33	26.5	2.9	0.36
1	400-010C	31	33.6	3.4	0.52
1 1/4	400-012C	25	42.2	3.6	0.71
1 1/2	400-015C	23	48.3	3.7	0.85
2	400-020C	20	60.3	3.9	1.13
2 1/2	400-025C	21	73.0	5.2	1.79
3	400-030C	18	88.9	5.5	2.34
4	400-040C	15	114.3	6.0	3.34
6	400-060C	12	168.3	7.1	5.88
8	400-080C	11	219.1	8.2	8.88
10	400-100C	10	273.1	9.3	12.61
12	400-120C	9	323.9	10.3	16.66
14	400-140C	9	355.6	11.1	20.75
16	400-160C	9	406.4	12.7	27.08

Corzan Pipe Schedule 80

3 & 6 metre lengths.

Size	Code	Maximum Pressure (bar)	O.D. (mm)	Minimum Wall (mm)	Weight /m
1/4	800-002C	78	13.8	3.0	0.17
3/8	800-003C	63	17.2	3.2	0.23
1/2	800-005C	59	21.4	3.7	0.34
3/4	800-007C	48	26.5	3.9	0.45
1	800-010C	43	33.6	4.6	0.67
1 1/4	800-012C	36	42.2	4.9	0.92
1 1/2	800-015C	32	48.3	5.1	1.12
2	800-020C	28	60.3	5.5	1.55
2 1/2	800-025C	29	73.0	7.0	2.36
3	800-030C	26	88.9	7.6	3.17
4	800-040C	22	114.3	8.6	4.63
6	800-060C	19	168.3	11.0	8.84
8	800-080C	17	219.1	12.7	13.49
10	800-100C	16	273.1	15.1	20.02
12	800-120C	16	323.9	17.5	27.52
14	800-140C	15	355.6	19.1	33.13
16	800-160C	15	406.4	21.4	42.60
18	800-180C	15	457.2	23.8	55.79

Please note: This information is based on current manufacturers details, and is subject to change without notification.