


## Fittings



Code: 006

- Tee
- short spigot
- injection moulded
- Butt + IR-welding
- PP Pure grey

Dimension	Code	Detail	da(OD) mm	s mm	z mm	L mm	L3 mm	Weight
20	72.006.0020.11	20X1,9 SDR11 ISO S-5	20	1,9	34	68	17,5	0.012
25	72.006.0025.11	25X2,3 SDR11 ISO S-5	25	2,3	40	80	20,5	0.021
32	72.006.0032.11	32X2,9 SDR11 ISO S-5	32	2,9	45	90	20,5	0.038
40	72.006.0040.11	40X3,7 SDR11 ISO S-5	40	3,7	50	100	20,5	0.06
50	72.006.0050.11	50X4,6 SDR11 ISO S-5	50	4,6	60	120	23	0.112
63	72.006.0063.11	63X5,8 SDR11 ISO S-5	63	5,8	72	144	25	0.221
75	72.006.0075.11	75X6,8 SDR11 ISO S-5	75	6,8	75	152	15	0.392
90	72.006.0090.11	90X8,2 SDR11 ISO S-5	90	8,2	105	213	38	0.664
110	72.006.0110.11	110X10,0 SDR11 ISO S-5	110	10	122	253	51	1.199
125	72.006.0125.11	125X11,4 SDR11 ISO S-5	125	11,4	140	280	52	1.7
140	72.006.0140.11	140X12,7 SDR11 ISO S-5	140	12,7	152	305	53	2.438
160	72.006.0160.11	160X14,6 SDR11 ISO S-5	160	14,6	173	346	57	3.4
180	72.006.0180.11	180X16,4 SDR11 ISO S-5	180	16,4	186	372	57	4.361
200	72.006.0200.11	200X18,2 SDR11 ISO S-5	200	18,2	200	405	57	6.02
225	72.006.0225.11	225X20,5 SDR11 ISO S-5	225	20,5	222,5	445	57	8.035
250	72.006.0250.11	250X22,7 SDR11 ISO S-5	250	22,7	235	470	72	10.96
280	72.006.0280.11	280X25,4 SDR11 ISO S-5	280	25,4	270	540	80	15
315	72.006.0315.11	315X28,6 SDR11 ISO S-5	315	28,6	275	550	80	19.26